

Smartflex

Tecnologia touchless

Touchless technology

Silenzioso

L'impiego di tecnologia all'avanguardia e di meccanica lineare di ultima generazione permettono al sistema Smartflex di azionare le porte automatiche, con sensori di presenza, in maniera totalmente silenziosa. Il comfort acustico assoluto rende l'esperienza di acquisto estremamente piacevole.

Veloce

Avvicinandosi all'unità, Smartflex si apre in modo automatico, rapido ed efficiente senza alcuna perdita di tempo.

Affidabile

Durante gli stress test il sistema Smartflex ha superato un milione di cicli di apertura.

Versatile

Grazie alle possibili regolazioni del sensore di presenza, il sistema Smartflex si rivela versatile adattandosi a diverse variabili. È possibile infatti regolare la distanza e la larghezza del raggio di intervento del sensore e il tempo di chiusura delle porte.

Silent

The use of state-of-the-art technology and the latest generation of linear mechanics allow the Smartflex system to operate automatic doors, with motion sensors, in complete silence. The absolute acoustic comfort makes the shopping experience extremely pleasant.

Fast

As you approach the unit, Smartflex opens automatically, quickly and efficiently without any loss of time.

Reliable

During stress testing, the Smartflex system passed one million opening cycles.

Versatile

Thanks to the possible adjustments of the presence sensor, the Smartflex system proves to be versatile by adapting to different variables. In fact, it is possible to adjust the distance and width of the sensor's range and the doors closing time.



Meno barriere, più vendite

L'acquisto d'impulso da sempre guida le scelte dei consumatori. Un espositore murale aperto non interpone barriere tra il consumatore e il prodotto. Un espositore chiuso da porte in vetro, invece, garantisce risparmio energetico e sostenibilità ambientale.

Smartflex racchiude in sé i vantaggi di entrambi i sistemi e contemporaneamente li supera: aprendosi in maniera rapida, efficiente e silenziosa spettacolarizza l'esperienza d'acquisto, attrae il consumatore e ne accresce la naturale predisposizione all'acquisto.

No barriers, more sales

Impulse buying has always driven consumer choices. An open wall display puts no barriers between the consumer and the product. A display closed by glass doors, on the other hand, guarantees energy saving and environmental sustainability.

Smartflex encompasses the advantages of both systems and simultaneously surpasses them: by opening quickly, efficiently and quietly, it enhances the shopping experience, attracts the consumer and increases their natural predisposition to buy.



Guarda il video di Smartflex in azione!

Watch the video of Smartflex in action!



Glass door

Open front

Smartflex

	Glass door	Open front	Smartflex
Risparmio energetico Energy saving	● ● ● ● ●	●	● ● ● ● ●
Acquisto d'impulso Impulse purchasing	● ●	● ● ● ● ●	● ● ● ● ●
Coinvolgimento del cliente Customer engagement	●	●	● ● ● ● ●
Riduzione dell'ingombro Reduced footprint	●	● ● ● ● ●	● ● ● ● ●
Acquisti simultanei Simultaneous shopping	● ●	● ● ● ● ●	● ● ● ● ●
Grab & Go Grab & Go (one hand shop)	●	● ● ● ● ●	● ● ● ● ●
Comfort del cliente Customer comfort	● ● ● ● ●	●	● ● ● ● ●
Comfort dell'operatore Operator comfort	● ● ● ● ●	●	● ● ● ● ●
Visibilità dei prodotti Product visibility	● ●	● ● ● ● ●	● ● ● ● ●
Aperture adattive Adaptive openings	●	●	● ● ● ● ●

● ● ● ● ● Migliori prestazioni / best performance

Smartflex

Più spazio per i tuoi clienti

More space for your customers



Nessun ingombro in corsia

Smartflex è la soluzione ideale per locali di piccole dimensioni e corsie ridotte. *Smartflex* consente infatti di avere un layout perfettamente ottimizzato in termini di ingombro delle corsie e di offrire ai clienti un'esperienza di shopping eccezionale.

Reduced footprint

Smartflex is the ideal solution for small premises and narrow aisles. Smartflex provides a layout that is perfectly optimized in terms of footprint of the aisle and offers customers an exceptional shopping experience.



Galaxy Smartflex

Carne • Sandwiches • Bevande • Latticini • Prodotti freschi
Meat • Sandwiches • Drinks • Dairy • Fresh products

H 205

P 88

L 94 • 125 • 188 • 250

Installazione

- Plug-in
- Remoto (optional)

Configurazione

5 ripiani regolabili in altezza

Refrigerante

R290

Refrigerazione

Ventilata

Classe di temperatura del prodotto

M1 (-1/+5 °C)

Classe climatica

3

Compressore

Ermetico

Sbrinamento

Fermata compressore

Fianchi

- Panoramici con vetro temprato (Spessore 25 mm)
- Specchio (Spessore 34 mm)
- Ciechi (Spessore 34 mm)

Interno

- Acciaio inox lucido o satinato
- Acciaio verniciato

Sistema di chiusura

Smartflex

Illuminazione

- LED superiore (3000 K, 4000 K, 5700 K, Rosa)
- LED ripiani (optional) (3000 K, 4000 K, 5700 K, Rosa)

Movimentazione

- Piedini regolabili in altezza
- Ruote pivotanti con freno (optional)

Installation

- Plug-in
- Remote (optional)

Configuration

5 shelves height adjustable

Refrigerant

R290

Refrigeration

Ventilated

Product temperature class

M1 (-1/+5 °C)

Climatic class

3

Compressor

Hermetic

Defrost

Off cycle

Side panels

- Panoramic with safety glass (25 mm thickness)
- Mirrored (34 mm thickness)
- Blind (34 mm thickness)

Inside

- Polished or satin stainless steel
- Painted steel

Closing system

Smartflex

Lighting

- LED on canopy (3000 K, 4000 K, 5700 K, Pink)
- Undershelf LED (optional) (3000 K, 4000 K, 5700 K, Pink)

Equipment handling

- Adjustable feet
- Swivel casters with brake (optional)



Colori disponibili

Available colours

Interno

Inside

-  RAL
-  Acciaio Inox / Stainless steel

Fronte

Front

-  RAL
-  Acciaio Inox / Stainless steel

Fianchi

Side panels

-  RAL
-  Acciaio Inox / Stainless steel

Disponibile
nella versione built-in

Also available
in a built-in version

Galaxy Smartflex			94 TN RV	125 TN RV	188 TN RV	250 TN RV
Dimensioni esterne (LxPxH) External dimensions (LxDxH)	Spalle spessore 25 mm Sides 25 mm thick	Piedini regolabili Adjustable feet	993x908x2054 mm	1300x908x2054 mm	1935x908x2054 mm	2550x908x2054 mm
		Ruote Pivottanti Swivel casters	993x908x2123 mm	1300x908x2123 mm	1935x908x2123 mm	2550x908x2123 mm
	Spalle spessore 34 mm Sides 34 mm thick	Piedini regolabili Adjustable feet	1011x908x2054 mm	1318x908x2054 mm	1953x908x2054 mm	2568x908x2054 mm
		Ruote Pivottanti Swivel casters	1011x908x2123 mm	1318x908x2123 mm	1953x908x2123 mm	2568x908x2123 mm
Capacità (lorda/netta) Capacity (gross/net)			596/355 lt	754/453 lt	1129/665 lt	1940/1164 lt
Peso (netto) Weight (net)			285 kg	345 kg	485 kg	650 kg
Area espositiva Total Display Area (TDA)			2,34 m²	2,75 m²	3,59 m²	4,52 m²
Refrigerazione Refrigeration			Ventilata Ventilated			
Refrigerante Refrigerant			R290			
Sbrinamento Defrost			Fermata compressore Off cycle			
Classe di temperatura del prodotto Product temperature class			M1 (-1 / +5 °C)			
Classe climatica Climate class			3 (25°C / 60% RH)			
Classe energetica Energy class						

DATI ELETTRICI - Dati tecnici riferiti a modelli con unità condensatrice a bordo ad aria plug-in R290, illuminazione LED superiore, ripiani non illuminati, spalle panoramiche, chiusura con smartflex.

ELECTRICAL DATA - Technical sheet about models with plug-in air-cooled on-board condensing unit R290, LED canopy lighting, non-illuminated shelves, panoramic end side panels, smartflex closing system.

Compressore (q.tà - tipologia) Compressor (q.ty - type)	1 Ermetico 1 Hermetic		2 Ermetici 2 Hermetics	
Alimentazione Power supply	230 V / 1 Ph / 50 Hz			
Assorbimento elettrico (regime) Electrical input (nominal)	1500 W / 8 A	1500 W / 8 A	2900 W / 16 A	3000 W / 16 A
Assorbimento elettrico (sbrinamento) Electrical input (defrost)	365 W / 1,7 A	150 W / 0,7 A	300 W / 1,4 A	300 W / 1,4 A

ALLESTIMENTO SETUP

Dimensioni ripiani (LxP)	940x350 mm	1250x350 mm	2x(940x350) mm	2x(1250 x 350) mm
Dimensioni ripiani (LxP)	940x382 mm	1250x382 mm	2x(940x382) mm	2x(1250 x 382) mm

