

Okys 2

Carni • Sandwiches • Bevande • Latticini • Prodotti freschi • Surgelati e gelati
Meat • Sandwiches • Drinks • Dairy • Fresh Products • Frozen Food & Ice-Cream

H 94

P 102

L 150 • 210 • 250

Installazione
Plug-in

Configurazione
Quadro comandi elettronico

Refrigerante
R290

Refrigerazione
Ventilata

Classe di temperatura del prodotto
• M1 (-1/+5 °C)
• L1 (-18/-15 °C)

Classe climatica
3

Compressore
Ermetico

Sbrinamento
Gas caldo

Fianchi
Triplo vetro camera

Interno
Acciaio verniciato

Sistema di chiusura
• Scorrevoli slide
• Scorrevoli push

Illuminazione
• LED 4000 K
• LED 5700 K
• LED Rosa

Movimentazione
Piedini fissi

Installation
Plug-in

Configuration
Electronic control board

Refrigerant
R290

Refrigeration
Ventilated

Product temperature class
• M1 (-1/+5 °C)
• L1 (-18/-15 °C)

Climatic class
3

Compressor
Hermetic

Defrost
Hot Gas

Side panels
Triple pane insulated glass

Inside
Painted steel

Closing system
• Sliding doors
• Push-open sliding lids

Lighting
• LED 4000 K
• LED 5700 K
• LED Pink

Equipment handling
Fixes feet

Colori disponibili
Available colours

Interno
Inside

 Bianco / White

 RAL

Esterno
Outside

 Bianco / White

 RAL

Basamento
Plinth

 RAL



Okys 2	150 TB/TN RV	210 TB/TN RV	250 TB/TN RV
Dimensioni esterne (LxPxH) External dimensions (LxDxH)	1500x1023x938 mm	2100x1023x938 mm	2500x1023x938 mm
Capacità (lorda/netta) Capacity (gross/net)	534 / 287 lt	779 / 418 lt	941 / 505 lt
Peso (netto) Weight (net)	187 kg	274 kg	316 kg
Area espositiva Total Display Area (TDA)	1,63 m ²	2,21 m ²	2,56 m ²
Refrigerazione Refrigeration	Ventilata Ventilated		
Refrigerante Refrigerant	R290		
Sbrinamento Defrost	Gas caldo Hot gas		
Classe di temperatura del prodotto Product temperature class	M1 (-1/+5 °C) L1 (-18/-15 °C)		
Classe climatica Climate class	3 (25°C / 60% RH)		
Classe energetica Energy class			

DATI ELETTRICI - Dati tecnici riferiti a modelli con unità condensatrice a bordo ad aria plug-in R290, illuminazione LED 5700K, chiusura con scorrevoli in vetro.
ELECTRICAL DATA - Technical sheet about models with plug-in air-cooled on-board condensing unit R290, LED lighting 5700K, closing system sliding glass lids.

Compressore (q.tà - tipologia) Compressor (q.ty - type)	2 Ermetici 2 Hermetics		
Alimentazione Power supply	230 V / 1 Ph / 50 Hz		
Assorbimento elettrico (regime) Electrical input (nominal)	830 W / 5 A	950 W / 5,1 A	1100 W / 5,3 A
Assorbimento elettrico (sbrinamento) Electrical input (defrost)	1120 W / 6 A	1850 W / 8,6 A	1880 W / 8,8 A

